

Gudy Roller DOT

General information

- removable transparent transfer adhesive
- using Neschen DOTEQ-technologie
- point-shaped adhesive application allows very easy application
- easy bubble-free bonding
- sticks clean, fast and is removable
- tear- resistant PET-tape
- solvent-free

Areas of application

- suitable for application of paper, cardboard and photos

Advantages / Special Features

- acid-free acrylic based adhesive, no blur
- PAT-tested and approved for picture archiving
- lignin-free
- in accordance with ISO 18932
- also available as refill, for practical refilling of the Roller Dots
- more information and an overview about Neschen products you can find at www.neschen.de

packaging units

- 12 blister per Display box; 12 boxes per carton
- 300 Dispenser in carton (bulk)
- Refill: Display-Box packed, with 12 blister packs with 2 refill dispensers each

Technische Daten / Technical Data

Kleber / Adhesive

Basis / Adhesive type	Polyacrylat Dispersion, lila eingefärbt, Tüpfel polyacrylate dispersion, lila-coloured, dots		
pH-Wert / pH-value	ca. / approx. 7,0		
Klebkraft / Adhesive strength [N/25 mm]	10 min: > 0,5	24h: > 0,5	AFERA 4001

Abdeckung / Masking

Materialtyp / Type	PET-Folie transparent, farblos, beidseitig silikonisiert PET-film, transparent, colourless, both sided siliconised	
Dicke / Thickness [µm]	36	approx. 1.4 mil
Flächengewicht / Weight [g/m²]	52	

Weitere Angaben / Others

Lagerbedingungen / Storage conditions	18° - 25°C/ 64 - 77°F; 40 bis 65% relative Luftfeuchtigkeit / relative humidity
Lagerzeit [Jahre] / Shelf Life [Years]	1
Raumbedingungen beim Verarbeiten/ indoor conditions for processing	5 - 40°C/ 41- 104°F

All tests were performed in accordance with 23/50-2, DIN 50014.

TECHNICAL SHEET

