

# DOBBELTKLÆBER HVID FOAM

## FM3032 - Polyethylene White Foam

### Description:

This works great on various substrates and offers permanent bonding to metals, woods, or plastics. It is very easy to bond two different forms of irregular surfaces together with this white foam.

### Features:

- Permanent bond
- Highly conformable
- Easily die cut
- White in color



Product Data			
<b>Carrier</b>	Closed Cell/ Cross Linked PE Foam	-	-
<b>Adhesive (each side)</b>	Acrylic	1.5 mil	0.04 mm
<b>Liner</b>	White glassine paper	-	-
<b>Total Tape Thickness</b>		31.49 mil	0.8 mm
<b>Peel Adhesion</b>	To Stainless Steel	63.5 oz/in	17.6 N/25 mm
<b>Tensile Strength</b>	-	76.5 oz/in	21 N/25 mm
<b>Elongation</b>	-	265%	
<b>Tear Strength</b>	-	685.5 oz/in	188 N/25 mm
<b>Service Temperature Range</b>	-	-22° - 194°F	-30°C- 90°C
<b>VOC Content</b>	-	2.2 g/L	
<b>Recommended Industry</b>	Framing	Awards	Signs Trophies

### Application Notes:

Indoor bonding of plastics, metals, woods, sound attenuation, cushioning or spacer applications and lightweight shim. Similar to 3M 4008, 3M 4016, and 3M 4032.

To achieve ultimate adhesion, the bonding surface should be dry, clean and free of dirt and oils. The strength of the adhesive bond is dependent on the amount of surface area directly contacting the adhesive. Firm pressure is recommended to obtain good adhesive to surface contact.

†Note: Values should not be used for specification purposes. Each user should make their own test to determine the products suitability for their own intended use and shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (21°C) with 50% relative humidity

# TECHNICAL SHEET

