

Øko-mount Print

TECHNICAL SHEET

Height / Dimensions	Unit	2400x1200 mm	2400x1600 mm	3000x1600 mm
10 mm	/	3125616	3125618	3125619
16 mm	/	3125620	3125622	3125623
Squareness	mm	+ 3	+ 3	+ 3

Tolerances	Unit	Values
Lenght	mm	+ - 3
Width	mm	+ - 2
Tickness	mm	+ - 0.3

Thickness	10 mm	16 mm
Weight	1.2 kg/m ²	1.5 kg/m ²

Parameter	Unit	All thickness
Liner		White coated
Core		Recycled paper
Recyclability	%	100
Moisture content	%	<11
Glue		PVaC
Compression resistance	Ton/m ²	25
Shipping units		Maximum 2 pallets on top of each other
Storage instructions		Temperature 8-25°C, humidity 55-65%
Whiteness	%	93.5 (iso 11475)
Brightness	%	85 (iso 2470-1)
Smoothness PPS10	µm	1 (iso 8791-4)
Gloss	%	40 (iso 8254-1)
Plotter possibilities		Cut, Crease, Slit-score, Cookie-Cut
Printability		Suited for digital printing / screen printing
Applications		Promotional and decorative applications, Single use, short term, small to medium sized applications.

Test 's Condition : 22°C and 50% humidity

